CAMBIA

made in HOLLAND

INTER NOVA
PROFESSIONAL LIGHTING

Housing	Aluminium, die cast
Fixture type	3-phase track light
Module	Luminus LED
Driver	Powergear® Ultimate adapter with build-in LED driver
Lumen output	1100lm, 2000lm
CCT	3000K, 4000K
CRI	>90Ra
Beam angles	10º - 60º (adjustable beam angle)
Adapter	Powergear® 3-phase ultimate adapter included
Rotatable	350º
Tiltable	90º
Expected Lifetime	>40.000h (L70/B30)
Photobiological safety	RG1 unlimited
Power factor	> 0.9
LOR	> 90%
Colour consistency	3 SDCM
Warranty	3 years warranty on LED module and driver

Net Weight	Dimensions carton L x W x H	Qty outer carton
750 grams	20 x 19 x 12 cm	20

LED MODULES

Standard

OPTIONS

Dimmable Casambi

LED MODULE OPTIONS

Description	Lumen	Watt	Lm/W	CCT	CRI	Description	Lumen	Watt	Lm/W	CCT	CRI
Luminus LED	1500lm	19W	79	930, 940	>90Ra						

LED modules
Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K
Premium White (PW): for fresh white and depth of colour in retail environments
[1]) Lumen output of LED module (COB)
[2]) Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT. The power of the complete fixture will be slightly higher due to the power consumption of the driver.
[3]) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.
Technical data can be changed by Internova without prior notice.

It all starts with light